

Technical Data Sheet

Product Code



BF-Ind-SC-10

BF-Ind-TC-10

BF-Ind-TC-15

Product Description

Dasso strand woven bamboo industrial flooring is made of 4 to 6 years' high-quality bamboo as raw material, and then bundled the small strand woven bamboo strips together with tape like below drawing showed. The floor installer glues them on the subfloor, sands off the tape, fills the gapes and finishes the surface. Being made of such small strips, the floor is very stable.

Product Technical Specification and Tolerance

product code	BF-Ind-SC-10/BF-Ind-TC-10/BF-Ind-TC-15
Properties	Standard
Dimension	300mm x 200mm x 10 mm CV / strand woven 280mm x 140mm x 10 mm CV/ traditional carbonized, unfinished 280mm x 140mm x 15 mm CV/ traditional carbonized, unfinished
Density/Specific Gravity	1100 kg/cm ³ - strand woven 650 kg/cm ³ - CV
Moisture content	6-10%
Hardness	55.2MPa (GB/T 17657-2013)
Slip Resistance	USRV58 (Standard: En1339-2003)
Reaction to Fire	class 1(critical radiant flux: 0.5w/cm ²)
Breaking Strength	22.4KN and 600mm
Termite resistance level	class 8 (Standard: NY-T1153.4-2006)

Use class	class 1 (Standard:EN335)
Mould resistance level	class I (Standard:NY-T1153.4-2006)
Warping	≤ 6mm and quantity is less than 10%.
Packaging and label	According to packaging layout drawing, check the label

Storage

- The warehouse should be well ventilated, with relative humidity from 45 to 75% at temperatures ranging from 50°F (+10°C) to 104°F (+40°C).
- Do not store product in pest infested and/or unsuitable warehouse.
- Leave the products in its original package when not in use, cover the bundles from top and bottom to avoid the influence of climatic events and other environmental hazards.
- Store the product horizontally on the ground with pallet shoe on every pallet. The bottom pallet should be placed on an even footing on spacer-pads or palettes. The maximum height of stacked bundles should not exceed 4.5 m.
- The difference between the spacers should not be more than 600mm, with distance of starting and ending spacer from the edge of the bundle not exceeding 200mm (the number of spacers should not be less than 3).