

## Technical Data Sheet

### ( Classy Middle-crossed Bamboo flooring)

Product code	Size
BF-TCH/TCV-154	L1960*W154*T15

#### Product Description

History, traditional bamboo was manufactured in different colors, natural and carbonized and 2 structures, horizontal and vertical for appearance. Dasso has expanded on the color options to produce numerous rich shades and hues to create many design options. The Horizontal structure is achieved by assembling small strips of bamboo in a flat position which clearly reveals the joints of the bamboo or stood on their edge to form a slender linear look. Either are perfect for the traditional bamboo appearance.

#### Product Technical Specification and Tolerance

Specifications Properties	Length/mm	Width/mm	Thickness/mm	T&G tolerance
Tolerance	±1	±0.2	±0.2	-0.15-0

Properties	Standard
Density/Specific Gravity	650 kg/cm <sup>3</sup>
Moisture content	6%-10%
Hardness	55.2MPa(GB/T 17657-2013)
Slip Resistance	USRV40 (CEN/TS15676)
Reaction to Fire	Dfl-s1 (EN 14342)
Breaking Strength	0.3KN (EN1533)
Packaging and label	According to packaging layout drawing, check the label

Biological and chemical Properties	Standard
Use class	UC 1(EN 335)
Release of Formaldehyde	E1(0.1mg/m <sup>2</sup> h) (GB/T17657-2013)

## Storage

- The warehouse should be well ventilated, with relative humidity from 45% to 75% at temperatures ranging from 50°F (+10°C) to 104°F (+40°C).
- Do not store product in pest infested and/or unsuitable warehouse.
- Leave the products in its original package when not in use, cover the bundles from top and bottom to avoid the influence of climatic events and other environmental hazards.
- Store the product horizontally on the ground with pallet shoe on every pallet. The bottom pallet should be placed on an even footing on spacer-pads or palettes. The maximum height of stacked bundles should not exceed 4.5 m.
- The difference between the spacers should not be more than 600mm, with distance of starting and ending spacer from the edge of the bundle not exceeding 200mm (the number of spacers should not be less than 3).