



Technical Data Sheet

dasso Interior Strand Woven Bamboo Flooring:

SKU: BF-SC-140

Product Description

Dasso Bamboo Interior Strand Woven Bamboo Flooring is made of crushed natural bamboo strip with high density. It has natural grain like wood, extremely hard and suitable for commercial and resident place.

Product Technical Specification and Tolerance

Properties	Standard
Dimension and Tolerance	L910*W127*T14
Density/Specific Gravity	1.13g /cm ³
Moisture content	7%
Surface Film Adhesion	1 grade (GB/T30364-2013)
Surface Impact Resistance	MAX : 6.3 no cracks
Surface Film Stain Resistance	No pollution, no corrosion
Surface Film Abrasion Resistance	Film remain on the surface after 100r of abrasion
Surface Film Abrasion Resistance	Abrasion value: 0.08g/100r
Release of Formaldehyde	0.1mg/L



Width of Swelling Rate	3.2%
Packaging and label	According to packaging layout drawing, check the label

Storage

- The warehouse should be well ventilated, with relative humidity from 45 to 75% at temperatures ranging from 50°F (+10°C) to 104°F (+40°C).
- Do not store product in pest infested and/or unsuitable warehouse.
- Leave the products in its original package when not in use, cover the bundles from top and bottom to avoid the influence of climatic events and other environmental hazards.
- Store the product horizontally on the ground with pallet shoe on every pallet. The bottom pallet should be placed on an even footing on spacer-pads or palettes. The maximum height of stacked bundles should not exceed 4.5 m.
- The difference between the spacers should not be more than 600mm, with distance of starting and ending spacer from the edge of the bundle not exceeding 200mm (the number of spacers should not be less than 3).