



Technical Data Sheet

dasso Bamboo Veneer:

SKU: BV-CV/CH-1 1/3 'X8'-0.6 ; BV-CV/CH-4 'X8'-0.6; BV-CV-1 1/3 'X10'-0.6; BV-CV-4 'X10'-0.6

Product Description

dasso Bamboo Veneer is a thin slice from laminated blocks made from bamboo strips, it is normally glued with structure panel (like plywood, particleboard...) to produce furniture or use like a decorative material on the top to create a natural appearance. Color is easy to be applied on, the color, size, thickness could be customized by preference.

Product Technical Specification and Tolerance

Properties	Standard
Dimension	2500*430/1250*0.6mm 3100*430/1250*0.6mm
Density/Specific Gravity	0.7g/cm ³
Top layer thickness / Wear layer	0.6 mm
Quilibrium MC	10% at 20°C and 65% rel. Air Humidity 8% at 20°C and 50% rel. Air Humidity
Resistance to Indentation - Brinell Hardness	depending on used substrate (EN 1534)
Formaldehyde emission	Class E1 (< 0.124 mg/m ³ , EN 717-1) / Class E0 (< 0,025 mg/m ³) 1)
Glue	D3 water resistant
Use class	Class 1 (Standard:EN335)
Warping	≤ 6mm and quantity is less than 10%.
Packaging and label	According to packaging layout drawing, check the label

Storage

- The warehouse should be well ventilated, with relative humidity from 45 to 75% at



temperatures ranging from 50°F (+10°C) to 104°F (+40°C).

- Do not store product in pest infested and/or unsuitable warehouse.
- Leave the products in its original package when not in use, cover the bundles from top and bottom to avoid the influence of climatic events and other environmental hazards.
- Store the product horizontally on the ground with pallet shoe on every pallet. The bottom pallet should be placed on an even footing on spacer-pads or palettes. The maximum height of stacked bundles should not exceed 4.5 m.
- The difference between the spacers should not be more than 600mm, with distance of starting and ending spacer from the edge of the bundle not exceeding 200mm (the number of spacers should not be less than 3).